PATENT Reply under 37 CFR 1.116

EXPEDITED PROCEDURE
Group 3733

AMENDMENT(S) TO THE CLAIMS

1. (Currently Amended) An orthopaedic reamer for cutting bone, comprising:

a rotatable shaft; and

a cutting head coupled with said shaft, said cutting head including a distal face with a

radius and a plurality of cutting teeth, each said cutting tooth including a pair of opposed side

walls extending from said distal face and a cutting edge extending between said side walls, each

said cutting edge including two corner segments and [[a]] at least one center segment extending

between said corner segments, said center segments being positioned relative to each other to

form a collective cutting profile at a substantially constant distance from said distal face of said

cutting head, said collective cutting profile comprising each of said center segments of said

plurality of cutting teeth.

2. (Currently Amended) The orthopaedic reamer of claim 1, wherein said at least one

center segment includes a single center segment having has a radius which is greater than a

radius of said corner segments.

3. (Previously Presented) The orthopaedic reamer of claim 1, wherein said at least one

center segment has a radius which is greater than a radius of said corner segments.

4. (Original) The orthopaedic reamer of claim 1, wherein said distal face has a radius of

between approximately 15 mm and 40 mm, and each said segment has a radius of between

approximately 14 mm and 39 mm.

SMI0100.US 2.

PATENT Reply under 37 CFR 1.116 EXPEDITED PROCEDURE Group 3733

5. (Original) The orthopaedic reamer of claim 1, wherein each said cutting tooth

includes a ramped portion extending between said cutting edge and said distal face.

6. (Original) The orthopaedic reamer of claim 5, wherein said ramped portion also

extends between said side walls.

7. (Original) The orthopaedic reamer of claim 1, wherein each said cutting tooth is

formed using a punching operation.

8. (Original) The orthopaedic reamer of claim 1, wherein said distal face is generally

hemispherical shaped.

9. (Currently Amended) A cutting head for an orthopaedic reamer, comprising a distal

face with a radius and a plurality of cutting teeth, each said cutting tooth including a pair of

opposed side walls extending from said distal face and a cutting edge extending between said

side walls, each said cutting edge including two corner segments and [[a]] at least one center

segment extending between said corner segments, said center segments being positioned relative to each other to form a <u>collective</u> cutting profile at a substantially constant distance from said

-----

distal face of said cutting head, said collective cutting profile comprising each of said center

segments of said plurality of cutting teeth.

10. (Currently Amended) The cutting head of claim 9, wherein said at least one center

segment includes a single center segment having has a radius which is greater than a radius of

SMI0100.US 3

respective said corner segments.

11. (Previously Presented) The cutting head of claim 9, wherein said at least one center

segment has a radius which is greater than a radius of said corner segments.

12. (Original) The cutting head of claim 9, wherein said distal face has a radius of

between approximately 15 mm and 40 mm, and each said segment has a radius of between

approximately 14 mm and 39 mm.

13. (Original) The cutting head of claim 9, wherein each said cutting tooth includes a

ramped portion extending between said cutting edge and said distal face.

14. (Original) The cutting head of claim 13, wherein said ramped portion also extends

between said side walls.

15. (Original) The cutting head of claim 9, wherein each said cutting tooth is formed

using a punching operation.

16. (Original) The cutting head of claim 9, wherein said distal face is generally

hemispherical shaped.

SMI0100.US 4